

Declaration of Performance (according to regulation EU No 305/2011)

Unique ID code **No. TSUK D32S load bearing RoofDek
D32S, 0.70, 0.90 & 1.20 mm, S280GD, PE15 Colorcoat
Lining Enamel
(component specification TQ 000-06-032-B)**

Harmonised standard

Intended use- **According to EN 1090-1:2009+A1:2011**
Load bearing RoofDek

Manufacturer **Tata Steel UK Limited
Shotton Works,
Deeside, Flintshire,
CH5 2NH
Tel: +44 (0)1244 892199
Website : www.tatasteeluk.com**

Authorised Representative **Mark Denys - Quality Director.
Tata Steel
Wenckebachstraat 1 .
Velsen Noord . 1951 JZ . NL .
PO Box 10.000 .
IJmuiden
1970 . CA. NL**

System of AVCP **System of assessment and verification of constancy of
performance of the product
System 2+**

Notified LRQA Nederland BV George Hintzenweg 77, 3068 AX
Rotterdam, Netherlands. No. 0343 performed the inspection of
the manufacturing plant, factory production control, the
continuous surveillance assessment and evaluation. The
performance of the product identified above is in conformity
with the set of declared performance/s. This declaration of
performance is issued under the sole responsibility of Tata
Steel UK limited

Signed for and on behalf of the manufacturer by:-



Jo Evans - Director, Building System UK
Tata Steel UK limited

Date:- 10/04/2025

Declared Performance/s

| Essential characteristic | Performance | Harmonised technical specification |
|--------------------------------------|-------------|------------------------------------|
| Tolerances on dimensions and shape | EN 1090-4 | EN 1090-1:2009+A1:2011 |
| Weldability | NPD | |
| Fracture toughness | NPD | |
| Reaction to fire | A1 | |
| Release of cadmium and its compounds | NPD | |
| Emission of radioactivity | NPD | |
| Durability | NPD | |
| Execution class (EXC) | EXC4 | |



0343 / CPR / LRQ00002892

Tata Steel
Strip Products UK

0343

TSUK D32S load bearing RoofDek

EN 1090-1:2009+A1:2011

D32S Load bearing RoofDek profile

To be used in - Load bearing Roof Deck

| | |
|---|-----------|
| Geometrical data (tolerances in dimensions and shape) | EN 1090-4 |
| Weldability | NPD |
| Fracture toughness of structural steel products | NPD |
| Reaction to fire | Class A1 |
| Release of cadmium and its compounds | NPD |
| Emission of radioactivity | NPD |
| Durability | NPD |
| Execution class (EXC) | EXC 4 |
| Structural characteristics -Design: | NPD |