

Declaration of Performance

(according to regulation EU No 305/2011)

Unique ID code

No. TSUK D35 load bearing RoofDek D35, 0.90 & 1.20 mm, AW-3004 H44 180 Rp0.2 MPa, ARS Finish D35, 0.90 & 1.20 mm, AW-3005 H27 195 Rp0.2 MPa, Mill and Stucco (component specification TQ 000-06-35-B)

Harmonised

standard Intended According to EN 1090-1:2009+A1:2011

Load bearing RoofDek

Manufacturer

Tata Steel UK Limited
Shotton Works,
Deeside, Flintshire,
CH5 2NH
Tel: +44 (0)1244 892199
Website: www.tatasteeluk.com

Authorised Representative Mark Denys - Quality Director.
Tata Steel
Wenckebachstraat 1.
Velsen Noord . 1951 JZ . NL .
PO Box 10.000 .
IJmuiden
1970 . CA. NL

System of AVCP

System of assessment and verification of constancy of performance of the product System 2+

Notified Body LRQA Nederland BV George Hintzenweg 77, 3068 AX Rotterdam, Netherlands. No. 0343 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Tata Steel UK limited.

Signed for and on behalf of the manufacturer by:-



Jo Evans - Director, Building System UK

Tata Steel UK Limited Date:- 10/04/2025

Declared Performance/s

Essential characteristic	Performance	Harmonised technical specification
Tolerances on dimensions and shape	EN 1090-5	
Weldability	NPD	
Fracture toughness	NPD	
Reaction to fire	A1	
Release of cadmium and its compounds	NPD	EN 1090-1:2009+A1:2011
Emission of radioactivity	NPD	
Durability	NPD	
Execution class (EXC)	EXC4	
Structural characteristics - Design:	NPD	



CE

0343 / CPR / LRQ00002892

Tata Steel Strip Products UK

0343

TSUK D35 load bearing RoofDek

EN 1090-1:2009+A1:2011

D35 Load bearing RoofDek profile

To be used in - Load bearing Roof Deck

Geometrical data (tolerances in dimensions and shape) EN 1090-5

Weldability

Fracture toughness of structural steel products NPD

Reaction to fire Class A1

Release of cadmium and its compounds NPD

Emission of radioactivity NPD

Durability NPD

Execution class (EXC) EXC 4

Structural characteristics -Design: NPD

Sensitivity: general