

Building Systems UK

Tata Steel Construction Solutions



FischerFIREPROOF®

Steel faced roof and wall panel systems with a mineral wool core

Building Systems UK has been a leading manufacturer and supplier of sustainable construction products in the UK for almost 70 years. We are now able to offer FischerFIREPROOF® mineral wool panel systems from Tata Steel Europe, manufactured in Germany, for outstanding fire and thermal performance in the UK construction sector.

Confidex® offers the most comprehensive guarantee for pre-finished steel products in Europe and provides peace of mind for up to 40 years. Unlike other guarantees Confidex® covers factory cut edges for the entirety of the guarantee period and does not require any inspections or maintenance to validate the guarantee, except when Colorcoat HPS200 Ultra® and Colorcoat Prisma® is used on a roof and wall that has a photovoltaic (PV) installation.



Benefits of the steel faced roof and wall mineral wool panel systems



Highly durable



Quick installation



Excellent fire resistance



Thermally efficient



Full traceability



Excellent weatherability



Robust guarantee



PV installation ready

FischerFIREPROOF® MW Plus

Steel faced architectural secret fix wall panel system with a mineral wool core

FischerFIREPROOF® MW Plus with secret fix fastening provides a clear external finish and enables reuse.

The panel system consists of two pre-finished steel sheets and a high-density mineral wool core. Depending on the application and required thermal insulation, panel thicknesses are available from 80 to 300 mm.

The standard panel width is 1000 mm, with additional widths available upon request. Colorcoat Prisma® and Colorcoat HPS200 Ultra® finishes are available.

Figure 1 - FischerFIREPROOF® MW Plus panel




Table 1 - Available thicknesses and U-values

Panel thicknesses	80	100	120	150	172	200	240	300
U-values	0.55	0.43	0.36	0.29	0.25	0.22	0.18	0.14

Fire performance

MW Plus panel systems are classified A2-s1,d0 according to the European Reaction to Fire classification system (Euroclasses) BS EN 13501-1 when tested on the internal face of the product.

Tata Steel have a library of fire resistance test evidence in accordance with BS EN 1364-1 and classifications in accordance with EN 13501-2. Design options for the application of MW Plus panel systems are considerable, therefore to obtain the correct specification to meet your project needs please [contact our technical department](#).




Figure 2 - MW Plus joint detail

FischerFIREPROOF® MW

Steel faced through fix wall panel system with a mineral wool core

FischerFIREPROOF® MW with through fix fastening.

The panel system consists of two pre-finished steel sheets and a high-density mineral wool core. Depending on the application and desired thermal insulation, panel thicknesses from 60 to 300 mm are available.

The standard panel width is 1100 mm, with other widths available upon request. Colorcoat Prisma® and Colorcoat HPS200 Ultra® finishes are available.

Figure 3 - FischerFIREPROOF® MW panel




Table 2 - Available thicknesses and U-values

Panel thicknesses	60	80	100	120	150	172	200	240	300
U-values	0.70	0.52	0.42	0.35	0.28	0.25	0.21	0.18	0.14

Fire performance

MW panel systems are classified A2-s1,d0 according to the European Reaction to Fire classification system (Euroclasses) BS EN 13501-1 when tested on the internal face of the product.

Tata Steel have a library of fire resistance test evidence in accordance with BS EN 1364-1 and classifications in accordance with EN 13501-2. Design options for the application of MW panel systems are considerable, therefore to obtain the correct specification to meet your project needs please [contact our technical department](#).




Figure 4 - MW joint detail

FischerFIREPROOF® MW D

Steel faced trapezoidal roof and wall panel systems with a mineral wool core

FischerFIREPROOF® MW D trapezoidal roof and wall panel.

The panel system consists of two pre-finished steel sheets and a high-density mineral wool core. Depending on the application and required thermal insulation, panel thicknesses from 100 to 280 mm (core thickness 60 to 240 mm) are available.

The standard panel width is 1000 mm. Colorcoat Prisma® and Colorcoat HPS200 Ultra® finishes are available.

Figure 5 - FischerFIREPROOF® MW D panel




Table 3 - Available thicknesses and U-values

Panel thicknesses (D)	100	120	140	160	190	212	240	280
U-values	0.65	0.50	0.40	0.34	0.28	0.24	0.21	0.18

PV Ready

MW D can be used under Photo Voltaic (PV) frame modules with no reduction in guarantee length ensuring all parts of the roof are covered for the same duration of the Confidex® Guarantee. For further information please [contact our technical department](#).




Figure 6 - MW D joint detail

Profile information

Options available for the facing sheets

A wide range of profiles are available to meet architectural project requirements and expand your design possibilities. This ensures that all your project's individual specifications can be met with confidence.


FischerFIREPROOF® MW & MW Plus

Outer pre-finished steel sheet


Microprofiling (V)
Microprofiling (M)
Profiling (L)
Flat (E)

Inner pre-finished steel sheet


Profiling (L)
Flat (E)



Microprofiling (V)




Microprofiling (M)



Profiling (L)



Flat (E)




FischerFIREPROOF® MW D

Outer pre-finished steel sheet



Trapezoidal profiling



Inner pre-finished steel sheet



Profiling (L)



Flat (E)



www.buildingsystemsuk.com

Trademarks

FischerFIREPROOF® is a registered trademark of Tata Steel Europe Limited.

Colorcoat HPS200 Ultra®, Colorcoat Prisma® and Confidex® are registered trademarks of Tata Steel UK Limited.

While care has been taken to ensure that the information contained in this publication is accurate, neither Tata Steel, nor its subsidiaries, accept responsibility or liability for errors or for information which is found to be misleading.

Before using products or services supplied or manufactured by Tata Steel and its subsidiaries, customers should satisfy themselves as to their suitability.

Copyright 2026

Tata Steel UK Limited

Building Systems UK

Shotton Works

Deeside

Flintshire

CH5 2NH

United Kingdom

T: +44 (0) 1244 892199

For sales and commercial enquiries:

E: bsukcommercial@tatasteeleurope.com

For technical enquiries:

E: technical.structuralproducts@tatasteeleurope.com

Registered Office: 18 Grosvenor Place, London, SW1X 7HS, Registered in England No. 02280000

Doc No: BSUK-E-0032-01