

Declaration of Performance

(according to Regulation EU No 305/2011)

Unique ID code TST Strongbox235JRH [Grade S235JRH / 1.0039]

Harmonised standard EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)

Intended use To be used in metal structures or in composite metal and concrete structures. This product is supplied with a non-specific inspection document 2.2 (according to EN 10204) that does not include the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is only suitable for intended uses for which the non-specific inspection 2.2 is sufficient.

Manufacturer TATA STEEL UK LIMITED
Registered in England No. 2280000
Registered office: 18 Grosvenor Place, London, SW1X 7HS, UK
Website : www.tatasteeluk.com

System of AVCP System of assessment and verification of constancy of performance of the product
System 2+ (FPC Certificate No: 0343/CPR/LRQ0840080/B)

Notified body Notified body No. 0343
LRQA Nederland B.V.
George Hintzenweg 77
3068 AX Rotterdam
The Netherlands

Table 1 – Essential characteristics and declared performances

Table 1 – Essential characteristics and declared performances				EN 10219-1:2006		
Essential characteristic	Performance			Harmonised technical specification		
Yield strength	Nominal thickness (mm)	Values Min (MPa)				
		235				
Tensile strength	Nominal thickness (mm)	Values (MPa)				
		min	max			
≤ 16	360	510				
Elongation (longitudinal)	Nominal thickness (mm)	Values min (%)				
		24 (22 or 17 where Table A.3 Note b applies)				
Impact strength (longitudinal)	Grade	Nom. Thk. (mm)	Impact Value min. average (J) at Test Temp (°C)			
	JRH	≤16	27J at +20°C			
Weldability (CEV)	Nominal thickness (mm)		Values max (%)			
	≤ 16		0.35			
Durability	Nominal thickness (mm)		Composition (cast) max.			
	≤ 16		C: 0.17 Mn: 1.40 P: 0.040 S: 0.040 N 0.009			
			FF deoxidation (a)			
	Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating					
Tolerances on dimensions and shape	Round, square, and rectangular hollow sections		In accordance with EN 10219-2:2006			

Notes: (a) FF – Fully killed steel containing nitrogen binding elements



0343

TATA STEEL UK LIMITED
Registered in England No. 2280000
Registered office: 18 Grosvenor Place, London, SW1X 7HS, UK

24

TST Strongbox235JRH [Grade S235JRH / 1.0039]

EN 10219-1:2006

To be used in metal structures or in composite metal and concrete structures. This product is supplied with a non-specific inspection document 2.2 (according to EN 10204) that does not include the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is only suitable for intended uses for which the non-specific inspection 2.2 is sufficient.

Performance declared for the following essential characteristics:

Yield strength: 235 MPa

Tensile strength: 360 – 510 MPa

Elongation: 24% (22% or 17% where Table A.3.b applies)

Impact strength: 27J at +20°C

Weldability (CEV): 0.35%

Durability: See Declaration of Performance

Tolerances on dimensions and shape: In accordance with EN 10219-2:2006

Dangerous Substances: No Performance Determined (NPD)



Dean Cartwright
Director, Technical
Tata Steel UK

Date 08/08/2025

Declaration of Performance

(according to The Construction Products (Amendment etc.) (EU Exit) Regulations 2020 No 1359)

Unique ID code TST Strongbox235JRH [Grade S235JRH / 1.0039]

Designated standard EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)

Intended use To be used in metal structures or in composite metal and concrete structures. This product is supplied with a non-specific inspection document 2.2 (according to EN 10204) that does not include the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is only suitable for intended uses for which the non-specific inspection 2.2 is sufficient.

Manufacturer TATA STEEL UK LIMITED
Registered in England No. 2280000
Registered office: 18 Grosvenor Place, London, SW1X 7HS, UK
Website : www.tatasteeluk.com

System of AVCP System of assessment and verification of constancy of performance of the product
System 2+ (FPC Certificate No: 0038/CPR/LRQ0840080/B)

Approved body Approved body No. 0038
LRQA Verification Limited
1 Trinity Park, Bickenhill
Birmingham, B37 7ES
UK

Table 1 – Essential characteristics and declared performances

Essential characteristic	Performance			Harmonised technical specification
Yield strength	Nominal thickness (mm)		Values Min (MPa)	EN 10219-1:2006
	≤ 16		235	
Tensile strength	Nominal thickness (mm)		Values (MPa)	
	≤ 16		minmax 360510	
Elongation (longitudinal)	Nominal thickness (mm)		Values min (%)	
	≤ 16		24 (22 or 17 where Table A.3 Note b applies)	
Impact strength (longitudinal)	Grade	Nom. Thk. (mm)	Impact Value min. average (J) at Test Temp (°C)	
	JRH	≤16	27J at +20°C	
Weldability (CEV)	Nominal thickness (mm)		Values max (%)	
	≤ 16		0.35	
Durability	Nominal thickness (mm)		Composition (cast) max.	
	≤ 16		C: 0.17 Mn: 1.40 P: 0.040 S: 0.040 N 0.009	
			FF deoxidation (a)	
	Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating			
Tolerances on dimensions and shape	Round, square, and rectangular hollow sections		In accordance with EN 10219-2:2006	

Notes: (a) FF = Fully killed steel containing nitrogen binding elements

Notes: (a) FF – Fully killed steel containing nitrogen binding elements

UK CA

0038

TATA STEEL UK LIMITED
Registered in England No. 2280000
Registered office: 18 Grosvenor Place, London, SW1X 7HS, UK

21

TST Strongbox235JRH [Grade S235JRH / 1.0039]

EN 10219-1:2006

To be used in metal structures or in composite metal and concrete structures. This product is supplied with a non-specific inspection document 2.2 (according to EN 10204) that does not include the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is only suitable for intended uses for which the non-specific inspection 2.2 is sufficient.

Performance declared for the following essential characteristics:

Yield strength: 235 MPa

Tensile strength: 360 – 510 MPa

Elongation: 24% (20% or 17% where Table A.3.b applies)

Impact strength: 27J at +20°C

Weldability (CEV): 0.35%

Durability: See Declaration of Performance

Tolerances on dimensions and shape: In accordance with EN 10219-2:2006

Dangerous Substances: No Performance Determined (NPD)



Dean Cartwright
Director, Technical
Tata Steel UK

Date 08/08/2025