

Declaration of Performance
According to The Construction Products (Amendment etc)
(EU Exit) Regulation 2020 No 1359

Unique ID code: No. TSUK S355J0C

Harmonised Standard: **Strip S355J0C / 1.0554**
According to EN 10025-1

Intended use: To be used in - welded, bolted and riveted structures

Manufacturer: Tata Steel UK Limited
 Port Talbot
 South Wales
 SA13 2NG
 Tel: +44 (0)1639 871111
 Website : www.tatasteeleurope.com

UK Approved Body
 LRQA Verification Ltd
 1, Trinity Park, Bickenhill Lane, Birmingham B37 7ES.
 Website : www.lrq.com

System of AVCP: System of assessment and verification of constancy of performance of the product
 System 2+

UK Approved Body LRQA Verification No 0038 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Tata Steel UK limited.

Signed for on behalf of the manufacturer by:-



Date- Sept 2023

Richard Sidebottom
 Director Mills, DSO & Technical
 Port Talbot – South Wales
 SA13 2NG -UK

Declared Performance

Essential characteristic	Performance		Harmonised technical specification
	Dimensions	EN 10051	
Tolerances on dimensions and shape			EN10025-1 2004
Yield strength (transverse)	Nominal thickness (mm)	Values Min (MPa)	
	> 16	355	
Tensile strength (transverse)	Nominal thickness (mm)	Values (MPa)	
	> 16	min max	
	- 3	510 680	
	3 16	470 630	
Elongation (transverse)	Nominal thickness (mm)	Values min (% , 80mm)	
	> 16	14	
	1 1.5	15	
	1.5 2	16	
	2 2.5	17	
	2.5 3	18	
	Nominal thickness (mm)	Values min (% , 5.65√s ₀)	
	3 16	22	
Impact strength (longitudinal)	J0	27J at +0°C	
Weldability CEV	Nominal thickness (mm)	Values max (%)	
	> 16	0.45	
Durability	Nominal thickness (mm)	Values max (%)	
	- <=16	C:0,20 Si: 0,55 Mn: 1,60 P: 0,030 S: 0,030 N: 0,012 Cu: 0,55	

**UK
CA**

0038

Tata Steel
UK

21

TSUK S355J0C 0038/CPR/LRQ0954218/E

EN 10025-1 – 2004

Strip S355J0C / 1.0554

To be used in - welded, bolted and riveted structures

Tolerances on dimensions : Strip EN10051

Elongation :
 Tensile Strength :
 Yield Strength : EN10025-2
 Impact Strength :
 Weldability :
 Durability :

Dangerous Substances : No Performance Determined


Declaration of Performance
(according to regulation EU No 305/2011)

Declared Performance

Unique ID code: No. TSUK S355J0C
Strip S355J0C / 1.0554
 Harmonised Standard: **According to EN 10025-1**
 Intended Use: To be used in - welded, bolted and riveted structures
 Manufacturer: Tata Steel UK Limited
 Port Talbot
 South Wales
 SA13 2NG
 Tel: +44 (0)1639 871111
 Website : www.tatasteeleurope.com
 Authorised Representative: Simon Edwards – Head of Quality
 Tata Steel NL
 Wenckebachstraat 1 .
 Velson Noord . 1951 JZ . NL . PO Box 10.000
 IJmuiden 1970 . CA. NL
 System of AVCP: System of assessment and verification of constancy of performance of the product
 System 2+

Notified Body LRQA Nederland B.V Inspection Services
 No. 0343 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Tata Steel UK limited

Signed for on behalf of the manufacturer by:-



Date- April 2024

Richard Sidebottom
 Director Mills, DSO & Technical
 Port Talbot – South Wales
 SA13 2NG -UK

Essential characteristic	Performance		Harmonised technical specification	
	Tolerances on dimensions and shape	Dimensions	EN 10051	
Yield strength (transverse)	Nominal thickness (mm)	Values Min (MPa)		
	> <=	355		
Tensile strength (transverse)	Nominal thickness (mm)	Values (MPa)		
	> < min max	510 680		
Elongation (transverse)	Nominal thickness (mm)	Values min (% , 80mm)		
	> <=	14		
Impact strength (longitudinal)	J0	27J at +0°C		
	3 16	22		
Weldability CEV	Nominal thickness (mm)	Values max (%)		
	> <=	0.45		
Durability	Nominal thickness (mm)	Values max (%)		
	- <=16	C:0,20 Si: 0,55 Mn: 1,60 P: 0,030 S: 0,030 N: 0,012 Cu: 0,55		

EN10025-1 2004



0343

Tata Steel
UK

13

TSUK S355J0C 0343/CPR/LRQ0954218/E

EN 10025-1 – 2004

Strip S355J0C / 1.0554

To be used in - welded, bolted and riveted structures

Tolerances on dimensions : Strip EN10051

Elongation :
 Tensile Strength :
 Yield Strength : EN10025-2
 Impact Strength :
 Weldability :
 Durability :

Dangerous Substances : No Performance Determined