

Declaration of Performance
According to The Construction Products (Amendment etc)
(EU Exit) Regulation 2020 No 1359

Unique ID
code

No. TSUK S235J2 Supplied +AR or +N

Strip S235J2 / 1.0117

Harmonised
Standard

According to EN 10025-1

Intended
use

To be used in - welded, bolted and riveted structures

Manufacturer

Tata Steel UK Limited
 Port Talbot
 South Wales
 SA13 2NG
 Tel: +44 (0)1639 871111
 Website : www.tatasteeleurope.com

UK Approved Body
 LRQA Verification Ltd
 1, Trinity Park, Bickenhill Lane, Birmingham B37 7ES.
 Website : www.lrq.com

System of
AVCP

System of assessment and verification of constancy of
 performance of the product
 System 2+

UK Approved Body LRQA Verification No 0038 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Tata Steel UK limited.

Signed for on behalf of the manufacturer by:-

Date- Sept 2023

Richard Sidebottom
 Director Mills, DSO & Technical
 Port Talbot – South Wales
 SA13 2NG -UK

Declared Performance

Essential characteristic	Performance		Harmonised technical specification	
	Tolerances on dimensions and shape	Dimensions	EN 10051	
Yield strength (transverse)	Nominal thickness (mm)	Values Min (MPa)		
	> <=	235		
Tensile strength (transverse)	Nominal thickness (mm)	Values (MPa)		
	> <=	min	max	
Elongation (transverse)	Nominal thickness (mm)	Values min (% , 80mm)		
	> <=	15		
Impact strength (longitudinal)	J2	27J at -20°C		
	Weldability CEV	Nominal thickness (mm)	Values max (%)	
Durability	Nominal thickness (mm)	Values max (%)		
	- <=16	C:0,17 Mn: 1,40 P: 0,025 S: 0,025 Cu: 0,55		

UK
CA

0038

Tata Steel
UK

21

TSUK S235J2 0038/CPR/LRQ0954218/E

EN 10025-1 – 2004

Strip S235J2 / 1.0117

To be used in - welded, bolted and riveted structures

Tolerances on dimensions : Strip EN10051

Elongation :
 Tensile Strength :
 Yield Strength : EN10025-2
 Impact Strength :
 Weldability :
 Durability :

Dangerous Substances : No Performance Determined

Declaration of Performance
(according to regulation EU No 305/2011)

Unique ID
code

No. TSUK S235J2 Supplied +AR or +N

Strip S235J2 / 1.0117

Harmonised
Standard

According to EN 10025-1

Intended Use

To be used in - welded, bolted and riveted structures

Manufacturer

Tata Steel UK Limited
Port Talbot
South Wales
SA13 2NG
Tel: +44 (0)1639 871111
Website : www.tatasteeleurope.com

Authorised
Representative

Simon Edwards – Head of Quality
Tata Steel NL
Wenckebachstraat 1 .
Velson Noord . 1951 JZ . NL . PO Box 10.000
IJmuiden 1970 . CA. NL

System of
AVCP

System of assessment and verification of constancy of
performance of the product
System 2+

Notified Body LRQA Nederland B.V Inspection Services
No. 0343 performed the inspection of the manufacturing
plant, factory production control, the continuous
surveillance assessment and evaluation. The performance
of the product identified above is in conformity with the set
of declared performance/s. This declaration of performance
is issued under the sole responsibility of Tata Steel UK
limited

Signed for on behalf of the manufacturer by:-

Date- April 2024

Richard Sidebottom
Director Mills, DSO & Technical
Port Talbot – South Wales
SA13 2NG -UK

Declared Performance

Essential characteristic	Performance		Harmonised technical specification	
	Dimensions	EN 10051		
Tolerances on dimensions and shape			EN10025-1 2004	
Yield strength (transverse)	Nominal thickness (mm)	Values Min (MPa)		
	> 16	235		
Tensile strength (transverse)	Nominal thickness (mm)	Values (MPa)		
	> 16	min max		
Elongation (transverse)	Nominal thickness (mm)	Values min (% , 80mm)		
	> 16	1		
	1	1.5		16
	1.5	2		17
	2	2.5		18
	2.5	3		19
	Nominal thickness (mm)	Values min (% , 5.65√so)		
3	16	24		
Impact strength (longitudinal)	J2	27J at -20°C		
Weldability CEV	Nominal thickness (mm)	Values max (%)		
	> 16	0.35		
Durability	Nominal thickness (mm)	Values max (%)		
	-	<=16	C:0,17 Mn: 1,40 P: 0,025 S: 0,025 Cu: 0,55	



0343

Tata Steel
UK

13

TSUK S235J2 0343/CPR/LRQ0954218/E

EN 10025-1 – 2004

Strip S235J2 / 1.0117

To be used in - welded, bolted and riveted structures

Tolerances on dimensions : Strip EN10051

Elongation :
Tensile Strength :
Yield Strength : EN10025-2
Impact Strength :
Weldability :
Durability :

Dangerous Substances : No Performance Determined