

Declaration of Performance
According to The Construction Products (Amendment etc)
(EU Exit) Regulation 2020 No 1359

Unique ID code	No. TSUK S355K2 Strip S355K2 / 1.0596
Harmonised Standard	According to EN 10025-1
Intended use	To be used in - welded, bolted and riveted structures
Manufacturer	Tata Steel UK Limited Port Talbot South Wales SA13 2NG Tel: +44 (0)1639 871111 Website : www.tatasteeluk.com
	UK Approved Body LRQA Verification Ltd 1, Trinity Park, Bickenhill Lane, Birmingham B37 7ES. Website : www.lrqa.com
System of AVCP	System of assessment and verification of constancy of performance of the product System 2+

UK Approved Body LRQA Verification No 0038 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Tata Steel UK limited.

Signed for on behalf of the manufacturer by:-

Date- Aug 2025

Dean Cartwright
 Director Technical Tata Steel UK
 Port Talbot – South Wales
 SA13 2NG -UK

Declared Performance

Essential characteristic	Performance		Harmonised technical specification
Tolerances on dimensions and shape	Dimensions	EN 10051	
Yield strength (transverse)	Nominal thickness (mm)	Values Min (MPa)	
	>	<=	
	-	16	355
Tensile strength (transverse)	Nominal thickness (mm)	Values (MPa)	
	>	<	min max
	-	3	510 680
	3	16	470 630
Elongation (transverse)	Nominal thickness (mm)	Values min (% , 80mm)	
	>	<=	
	-	1	12
	1	1.5	13
	1.5	2	15
	2	2.5	16
	2.5	3	17
	Nominal thickness (mm)	Values min (% , 5.65√s0)	
Impact strength (longitudinal)	3	16	22
	K2		40J at -20°C
Weldability CEV	Nominal thickness (mm)	Values max (%)	
	>	<=	
	-	16	0.45
Durability	Nominal thickness (mm)	Values max (%)	
	-	<=16	C:0.20 Si: 0.55 Mn: 1.60 P: 0.025 S: 0.025 Cu: 0.55

EN10025-1 2004

**UK
CA**

0038

Tata Steel
UK

21

TSUK S355K2 0038/CPR/LRQ0954218/E

EN 10025-1 – 2004

Strip S355K2 / 1.0596

To be used in - welded, bolted and riveted structures

Tolerances on dimensions : Strip EN10051

Elongation :
 Tensile Strength :
 Yield Strength : EN10025-2
 Impact Strength :
 Weldability :
 Durability :

Dangerous Substances : No Performance Determined

Declaration of Performance (according to regulation EU No 305/2011)

Declared Performance

Unique ID
code

No. TSUK S355K2

Strip S355K2 / 1.0596

Harmonised
Standard

According to EN 10025-1

Intended Use

To be used in - welded, bolted and riveted structures

Manufacturer

Tata Steel UK Limited
Port Talbot
South Wales
SA13 2NG
Tel: +44 (0)1639 871111
Website : www.tatasteeluk.com

System of
AVCP

System of assessment and verification of constancy of
performance of the product
System 2+

Notified Body LRQA Nederland B.V Inspection Services
No. 0343 performed the inspection of the manufacturing
plant, factory production control, the continuous
surveillance assessment and evaluation. The performance
of the product identified above is in conformity with the set
of declared performance/s. This declaration of performance
is issued under the sole responsibility of Tata Steel UK
limited

Signed for on behalf of the manufacturer by:-



Date- Aug 2025

Dean Cartwright
Director Technical Tata Steel UK
Port Talbot – South Wales
SA13 2NG -UK

Essential characteristic	Performance		Harmonised technical specification
Tolerances on dimensions and shape	Dimensions	EN 10051	
Yield strength (transverse)	Nominal thickness (mm)	Values Min (MPa)	
	> <=		
	- 16	355	
Tensile strength (transverse)	Nominal thickness (mm)	Values (MPa)	
	> <	min	max
	- 3	510	680
	3 16	470	630
Elongation (transverse)	Nominal thickness (mm)	Values min (% , 80mm)	
	> <=		
	- 1	12	
	1 1.5	13	
	1.5 2	15	
	2 2.5	16	
	2.5 3	17	
	Nominal thickness (mm)	Values min (% , 5.65√so)	
	3 16	22	
Impact strength (longitudinal)	K2	40J at -20°C	
Weldability CEV	Nominal thickness (mm)	Values max (%)	
	> <=		
	- 16	0.45	
Durability	Nominal thickness (mm)	Values max (%)	
	- <=16	C:0,20 Si: 0,55 Mn: 1,60 P: 0,025 S: 0,025 Cu: 0,55	

EN10025-1 2004



0343

Tata Steel
UK

13

TSUK S355K2 0343/CPR/LRQ0954218/E

EN 10025-1 – 2004

Strip S355K2 / 1.0596

To be used in - welded, bolted and riveted structures

Tolerances on dimensions : Strip EN10051

Elongation :

Tensile Strength :

Yield Strength :

Impact Strength :

Weldability :

Durability :

EN10025-2

Dangerous Substances : No Performance Determined