


Tata Steel retain the right to ammend the construction and technical specifications shown on this drawing without prior notice.



All support steelwork by others

TRISOBUILD™ U-VALUES

The depth below refers to both the minimum bracket & insulation height to achieve the stated 'U' value when using a LP1000 liner

Depth 140 = 0.30 W/m²K.	Depth 240 = 0.18 W/m²K.
Depth 160 = 0.26 W/m²K.	Depth 260 = 0.16 W/m²K.
Depth 180 = 0.23 W/m²K.	Depth 280 = 0.15 W/m²K.
Depth 200 = 0.21 W/m²K.	Depth 300 = 0.14 W/m²K.
Depth 220 = 0.19 W/m²K.	

Junction 'psi' and 'f' values

$\Psi =$  W/mK.  
 $f =$

Stated calculation results are dependent on components being as shown.  
Computer modeled in accordance with EN ISO 10211



**Building Systems UK**  
A Tata Steel enterprise

Technical Office - TEL : 01244 892199  
www.buildingsystemsuk.co.uk

PROJECT		Typical Trisobuild VW Details	
TITLE		Parapet	
DRAWN BY	LK	SCALE	NTS
APPROVED BY	PS	TOLERANCES	
DATE	01/06/23	DRG. No.	W1-016-02